



(19)

(11) Publication number: 0

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: 08057970

(51) Intl. Cl.: H01L 21/3065 B01J 3/02 C2:
4/00 H01L 21/203 H01L 21/2

(22) Application date: 14.03.96

(30) Priority: (43) Date of application publication: 22.09.97 (84) Designated contracting states:	(71) Applicant: TOSHIBA CORP (72) Inventor: KURIHARA KAZUAKI SEKINE MAKOTO OKUMURA KATSUYA (74) Representative:
---	---

(54) SEMICONDUCTOR
MANUFACTURING
EQUIPMENT

(57) Abstract:

PROBLEM TO BE SOLVED: To enhance usage efficiency of process gas under a decompressed atmosphere of an etching device, etc., and reduce production cost by a method wherein the process gas is supplied to the interior of a vacuum bath for discharging the inside and decompressing and a part of exhaust gas is recirculated from the exhaust side to the interior of the vacuum bath.

SOLUTION: A nozzle incorporated into an anode electrode 103 in a vacuum bath 101 is connected to a gas bomb 111 being a supply source of process gas, and the exhaust side 105a of a turbo-molecule pump connecting with the vacuum bath 101 is connected with a dry pump 106. Further, in the intermediate side of a

recirculation line 107 provided between the exhaust side 105a of the turbo- molecule pump and the vacuum bath 101, a valve 108 and a filter 113 are disposed. A part of the process gas discharged by a turbo- molecule pump 105 from inside of the vacuum bath 101 is returned to the vacuum bath 101 through the recirculation line 107. A ratio of this process gas recirculated is adjusted by the degree of opening of the valve 108.

COPYRIGHT: (C)1997,JPO

